



## Potato Peeler PI-10

**10 KG. / 22 POUNDS LOAD PER CYCLE.**

**Stainless steel construction commercial potato peeler.  
Also suitable to peel carrots and other similar products.**

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purposes.
- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

### TECHNICAL SPECIFICATIONS

Hourly production: 200 Kg / 240 Kg  
Capacity per load: 10 Kg  
Timer (min-max): 0' - 6'  
Single Phase: 550 W  
Three phase: 370 W

External dimensions (WxDxH)  
433 mm x 635 mm x 625 mm <m>

External dimensions with stand  
433 mm x 638 mm x 1040 mm <m>

Net weight: 36 Kg

Noise level (1m.): 70 dB(A)  
Background noise: 32 dB(A)

#### DEFAULT EQUIPMENT

- #### OPTIONAL EQUIPMENT
- Stainless steel floor stand.
  - Filter with no-foam feature.